
TECHNICAL SPECIFICATIONS – GLASS TILE

Interstyle's glass tile products are designed to be used in the same manner as ceramic wall tile. *Interstyle's* glass tile products are resistant to chemical attack, do not absorb water and do not discolor in normal environmental conditions. *Interstyle's* glass tile products are suitable for both interior and exterior installations including areas of continuous immersion in water and exposure to freezing conditions. *Interstyle* provides detailed installation instructions with all products.

Manufacturing Process

All of *Interstyle's* glass tile products are manufactured by fusing or combining colored ceramic glazes onto or with selected clear glass at temperatures of greater than 700°C. Most glass tile products incorporate a microporous structure onto the back of the tile to ensure good physical bond with normal tile setting materials.

Interstyle's glass wall tile products are manufactured to satisfy or exceed the appropriate requirements of American National Standard Specifications for Glass Tile ANSI A137.2.

Critical properties of *Interstyle's* glass tile:

Water Absorption	0% - Impervious	ASTM C373
Chemical Resistance	Unaffected	ASTM C650
Resistance to Freeze-Thaw	Unaffected	ASTM C1026
Resistance to Staining	Unaffected	ASTM C1378
Moh's Hardness	>4	

Warranty

Interstyle warrants its glass tile products to be free from manufacturing defects for the life of the product, subject to the following qualifications.



- Variations of color, shade and size are inherent of all burnt clay or glass materials. No claims with respect to color or shade variation will be accepted after installation. The buyer is responsible for the inspection and acceptance of our materials before they leave our warehouse.
- Installation materials and conditions may have a significant affect upon the performance of a glass tile installation, therefore finished installations are not warranted by *Interstyle*. Methods of installation are beyond our control and we do not accept responsibility for chipping, crazing, spalling, etching, cracking, discoloration or loosening from the setting bed. If our products are regarded as unsatisfactory for any reason, we must be notified before installation. No allowance will be made for labor, costs of replacement, or for any other charges after the materials have been installed.

